UnionTech

OnFocux600

Born for Prototyping

FLEXIBLE. EFFICIENT. INTELLIGENT.



Prototype





Automotive





Packaging




Home Appliances



Art Design





Prototype Parts Material: Tough Yellow Resin



Automobile Parts Material: Transparent Resin



Art Design Parts Material: Proto600 White Resin

UnionTech LTD

Email: mkt@uniontech3d.com Phone: +86 4001-388-966 Website: www.uniontech3d.com Room 102, Unit 40, 258 Xinzhuan Rd, 201612 Shanghai, China

UnionTech GmbH

Email: info@uniontech3d.de Phone: +49 (0) 6187-9913679 Website: www.uniontech3d.de Bleichstraße 8, 61137 Schöneck, Germany

Features

۲

0

Unionicch



12 rue Jean Bart 78960 Voisins le Bretonneux

Tel: + 33 (0)1 30 60 03 33 Email: devis@3dsolutions.fr www.3dsolutions.fr

High Precision

Unique laser scanning automatic calibration technology.

High Efficiency

With independent intellectual property rights of the light spot technology.

High Stability

Excellent motion control, liquid level control, temperature control system.

Highly Intelligent

UnionTech core algorithm, original galvanometer scanning path planning and exposure strategy algorithm.

Industry Original

Monitoring function, intelligent AI visual detection algorithm to ensure print stability.

Technical Data

Technology Type	Stereolithography (SLA)	Network Type and Protocol	WiFi Ethernet using MQTT/HTTP/TCP WiFi
Build Envelope Capacity	600 × 600 × 400 mm 23.6 × 23.6 × 15.7 in	Electrical Requirements	200-240 VAC, 50/60 Hz
Accuracy	L < 100 mm: ±0.1 mm L ≥ 100 mm: ±0.1% x L	Rated Power	2.6 kVA
Layer Thickness	0.05 - 0.25 mm	Systems Control	Closed-loop
Laser	Solid-state frequency tripled Nd: YVO4	Temperature Range	72–79 °F (22–26 °C)
Wavelength	355 nm	Relative Humidity	< 40%
Materials	All SLA Materials of 355 nm	Machine Size (W x D x H)	1375 × 1295× 1930 mm
Scanning Speed	8-15 m/s	Machine Weight	850 kg
Controlling Software	UnionTech™ RSCON	Accessories	Post-Curing Unit (optional)
Data Preparation Software	Polydevs Pro, BPC	Resin Tank	Fixed
Operating System	Windows 10	Certificates	CE / UKCA

* Specifications are subject to change. Consult with your sales representative for confirmation of current offering.